

Model		AI-W5.1-B combinations					
<b>Main Parameter</b>							
Battery Model Number		AI-W5.1-B	AI-W10.2-B	AI-W15.3-B	AI-W20.4-B	AI-W25.6-B	AI-W30.7-B
Number of battery units in parallel (Optional)		1	2	3	4	5	6
Battery Chemistry		LiFePO <sub>4</sub>					
Built-in Circuit Breaker		125A 2P, 60Vdc					
Battery Module Energy ( kWh )		5.12					
Battery Module Voltage ( V )		51.2					
Battery Module Capacity ( Ah )		100					
Nominal Voltage ( V )		51.2					
Operating Voltage ( V )		44.8 ~ 57.6					
Nominal Energy ( kWh )		5.12	10.24	15.36	20.48	25.6	30.72
Usable Energy ( kWh ) <sup>[1]</sup>		4.6	9.2	13.8	18.4	23	27.6
Rated DC Power ( KW )		2.5	5	7.5	10	12	12
Charge / Discharge Current ( A ) <sup>[2]</sup>	Recommend	50	100	150	200	250	250
	Max.	100	200	250	250	250	250
	Peak ( 10s, 25°C )	150	270	360	360	360	360
<b>Other Parameter</b>							
Recommend Depth of Discharge		90%					
System Dimension ( W × D × H, mm )		720×255×569	720×255×850	720×255×1131	720×255×1412	720×255×1693	720×255×1974
System Weight ( kg )		74.5	127.5	180.5	233.5	286.5	339.5
Battery Module Dimension ( W × D × H, mm )		720±3×254±1.5×300±1.5					
Battery Module Weight ( kg )		55					
MasterLED Indicator		Battery module : 3LED ( working, alarming, protecting ) , PDU module : 5LED ( SOC : 20% ~ 100% ) & 3LED ( working, alarming, protecting )					
IP Rating of Enclosure		IP65 ( after stacking )					
Operating Temperature		Charge : -20°C ~ 55°C / Discharge : -20°C ~ 55°C					
Standard charging method by manufacturer		Charge at 25±2°C at constant current 50A until the voltage reaches 57.6V.					
Standard discharging method by manufacturer		Discharge at 25±2°C at constant current 50A until the voltage reaches 44.8v.					
Storage Temperature		0°C ~ 35°C					
Humidity		5% ~ 95%, non-condensing					
Altitude		≤3000m					
Installation		Floor-Mounted					
Communication Port		CAN2.0, RS485					
Cycle Life		≥6000 ( 25°C±2°C , 0.5C / 0.5C, 90%DOD, 70%EOL )					
Energy Throughput		16MWh ( Battery Module @70%EOL )					
Warranty Period <sup>[3]</sup>		10 years					
Certification		UN38.3, IEC62619, CE, UK, VDE2510-50, CEI0-21,CE-LVD, CEC, FCC, UL1973, UL9540A					

[1]DC Usable Energy, test conditions: 90% DOD, 0.5C charge & discharge at 25°C . System usable energy may vary due to system configuration parameters.

[2]The current is affected by temperature and SOC.

[3]Conditions apply, refer to Deye Warranty Letter.

[4]Made in China.